

Tabelle1

Dienstag 15 April 2014 16:44:00:33139 VCDS Version: PCI 12.12.2  
 1K8 907 115 B 2.0l R4/4V TFSI 0030

Block A: '115					
	Zeit	Engine Speed (G28)	Engine Load	Boost Pressure (specified)	Boost Pressure (actual)
Markierung	MARKE	/min	%	mbar	mbar
	7.03	1480	14.3	270.0	1030.0
	7.08	1480	14.3	300.0	1030.0
	7.12	1480	14.3	350.0	1030.0
	7.17	1480	15.0	410.0	1030.0
	7.22	1480	17.3	470.0	1030.0
	7.28	1480	20.3	650.0	1030.0
	7.33	1480	24.1	890.0	1020.0
	7.37	1480	27.1	1090.0	1020.0
	7.42	1520	33.1	1340.0	1010.0
	7.47	1560	47.4	1500.0	1010.0
	7.51	1560	56.4	1510.0	1010.0
	7.56	1520	66.9	1500.0	1010.0
	7.61	1520	69.2	1480.0	1020.0
	7.65	1560	72.2	1480.0	1020.0
	7.70	1600	77.4	1480.0	1020.0
	7.75	1600	81.2	1480.0	1030.0
	7.81	1600	84.2	1480.0	1040.0
	7.86	1600	85.0	1480.0	1050.0
	7.90	1640	86.5	1500.0	1060.0
	7.95	1680	88.0	1510.0	1070.0
	8.00	1680	88.7	1510.0	1080.0
	8.04	1720	89.5	1520.0	1090.0
	8.09	1720	90.2	1530.0	1100.0
	8.14	1760	91.0	1540.0	1110.0
	8.18	1760	91.7	1540.0	1130.0
	8.23	1760	91.7	1550.0	1140.0
	8.28	1800	91.7	1570.0	1150.0
	8.34	1840	93.2	1580.0	1170.0
	8.39	1840	94.0	1600.0	1180.0
	8.43	1880	94.7	1620.0	1200.0
	8.48	1880	96.2	1640.0	1210.0
	8.53	1920	97.0	1660.0	1220.0
	8.57	1920	97.7	1680.0	1240.0
	8.62	1960	99.2	1690.0	1250.0
	8.67	2000	100.0	1730.0	1270.0
	8.72	2000	101.5	1750.0	1280.0
	8.76	2040	102.3	1790.0	1300.0
	8.81	2040	103.8	1830.0	1310.0
	8.87	2080	106.8	1870.0	1330.0
	8.92	2120	108.3	1910.0	1340.0
	8.96	2120	109.8	1960.0	1360.0
	9.01	2160	111.3	1990.0	1380.0
	9.06	2200	112.8	2030.0	1390.0
	9.10	2200	114.3	2060.0	1420.0
	9.16	2240	117.3	2110.0	1440.0
	9.20	2280	118.0	2110.0	1450.0
	9.24	2280	120.3	2110.0	1480.0
	9.29	2320	121.8	2110.0	1490.0
	9.34	2360	123.3	2110.0	1520.0
	9.41	2400	126.3	2120.0	1550.0
	9.45	2440	127.8	2120.0	1580.0

Tabelle1

9.50	2440	130.1	2120.0	1600.0
9.55	2480	132.3	2120.0	1630.0
9.59	2520	133.8	2120.0	1650.0
9.64	2560	136.1	2120.0	1690.0
9.69	2560	139.8	2120.0	1720.0
9.73	2600	142.1	2120.0	1750.0
9.78	2640	145.9	2120.0	1790.0
9.82	2680	147.4	2120.0	1820.0
9.87	2720	150.4	2120.0	1870.0
9.94	2760	154.9	2120.0	1930.0
9.98	2800	158.6	2120.0	1960.0
10.03	2840	162.4	2120.0	2000.0
10.07	2880	163.2	2120.0	2030.0
10.12	2920	164.7	2120.0	2050.0
10.17	2960	167.7	2120.0	2060.0
10.21	2960	168.4	2110.0	2060.0
10.26	3040	171.4	2110.0	2080.0
10.31	3080	173.7	2110.0	2090.0
10.35	3080	175.9	2110.0	2110.0
10.40	3120	175.9	2110.0	2110.0
10.46	3160	178.2	2110.0	2130.0
10.51	3240	180.5	2110.0	2130.0
10.56	3240	181.2	2110.0	2150.0
10.60	3280	182.0	2110.0	2160.0
10.65	3360	182.0	2100.0	2170.0
10.70	3400	185.0	2100.0	2190.0
10.74	3400	185.0	2100.0	2200.0
10.79	3480	185.0	2100.0	2200.0
10.84	3480	186.5	2100.0	2200.0
10.88	3560	185.0	2090.0	2190.0
10.93	3560	185.7	2090.0	2180.0
10.99	3640	185.0	2080.0	2170.0
11.04	3680	183.5	2080.0	2150.0
11.09	3680	183.5	2080.0	2140.0
11.14	3720	181.2	2070.0	2130.0
11.18	3760	181.2	2070.0	2110.0
11.23	3840	180.5	2080.0	2090.0
11.28	3880	178.2	2080.0	2080.0
11.32	3880	175.9	2080.0	2060.0
11.37	3960	175.2	2080.0	2040.0
11.42	3960	175.9	2080.0	2030.0
11.46	4000	174.4	2080.0	2030.0
11.52	4000	172.9	2080.0	2020.0
11.57	4080	172.9	2080.0	2020.0
11.62	4120	172.2	2080.0	2020.0
11.66	4160	172.2	2090.0	2030.0
11.71	4200	173.7	2100.0	2030.0
11.76	4200	175.2	2100.0	2030.0
11.80	4240	175.2	2100.0	2050.0
11.85	4280	175.9	2100.0	2050.0
11.90	4360	176.7	2100.0	2060.0
11.94	4400	178.2	2100.0	2070.0
11.99	4440	179.7	2100.0	2070.0
12.05	4480	181.2	2110.0	2080.0
12.10	4480	181.2	2110.0	2090.0
12.15	4520	180.5	2110.0	2100.0
12.19	4560	180.5	2110.0	2100.0
12.24	4600	179.7	2110.0	2090.0

Tabelle1

12.29	4640	178.9	2120.0	2090.0
12.34	4680	179.7	2110.0	2090.0
12.38	4720	178.9	2110.0	2080.0
12.43	4720	177.4	2110.0	2090.0
12.48	4800	176.7	2120.0	2090.0
12.52	4840	176.7	2110.0	2090.0
12.59	4880	177.4	2110.0	2090.0
12.63	4920	177.4	2110.0	2100.0
12.68	4920	177.4	2110.0	2100.0
12.73	4960	175.9	2130.0	2110.0
12.77	5000	175.9	2120.0	2100.0
12.82	5040	175.2	2120.0	2100.0
12.87	5080	175.2	2120.0	2100.0
12.91	5120	175.2	2120.0	2100.0
12.96	5160	175.9	2120.0	2090.0
13.01	5200	175.9	2110.0	2080.0
13.05	5200	175.9	2110.0	2080.0
13.12	5240	175.9	2110.0	2070.0
13.16	5280	173.7	2110.0	2070.0
13.21	5360	174.4	2110.0	2050.0
13.26	5400	172.2	2110.0	2040.0
13.31	5360	172.9	2110.0	2040.0
13.35	5400	172.2	2110.0	2020.0
13.40	5440	171.4	2100.0	2010.0
13.44	5520	169.9	2100.0	1990.0
13.49	5520	170.7	2090.0	1980.0
13.54	5560	169.2	2090.0	1980.0
13.58	5560	169.2	2090.0	1980.0
13.65	5600	170.7	2080.0	1990.0
13.69	5640	170.7	2080.0	1990.0
13.74	5680	171.4	2060.0	2000.0
13.79	5720	172.9	2060.0	2010.0
13.83	5720	172.2	2050.0	2020.0
13.88	5760	172.9	2050.0	2030.0
13.93	5800	173.7	2040.0	2020.0
13.98	5840	174.4	2030.0	2020.0
14.02	5880	174.4	2010.0	2020.0
14.07	5920	174.4	1990.0	2020.0
14.12	5920	175.2	1970.0	2020.0
14.18	5960	175.2	1960.0	2010.0
14.22	6000	174.4	1950.0	2010.0
14.27	6040	173.7	1940.0	2000.0
14.32	6080	172.2	1920.0	1990.0
14.37	6120	172.2	1910.0	1970.0
14.42	6160	171.4	1890.0	1960.0
14.46	6160	169.9	1890.0	1960.0
14.51	6200	169.9	1890.0	1950.0
14.56	6240	167.7	1880.0	1930.0
14.61	6240	166.9	1880.0	1920.0
14.66	6280	166.2	1870.0	1910.0
14.72	6320	165.4	1870.0	1900.0
14.77	6360	164.7	1860.0	1910.0
14.82	6360	163.9	1850.0	1910.0
14.87	6400	163.9	1850.0	1910.0
14.92	6440	162.4	1840.0	1900.0
14.97	6480	163.2	1840.0	1890.0
15.02	6480	162.4	1830.0	1880.0
15.07	6520	161.7	1830.0	1880.0

Tabelle1

15.12	6520	160.9	1820.0	1870.0
15.17	6600	159.4	1790.0	1860.0
15.22	6640	158.6	1780.0	1850.0
15.28	6640	159.4	1660.0	1840.0
15.33	6680	157.9	1620.0	1830.0
15.38	6720	157.9	1500.0	1830.0
15.43	6720	157.1	1360.0	1820.0
15.47	6760	155.6	1360.0	1820.0
15.52	6760	141.4	1290.0	1840.0
15.57	6800	139.8	1220.0	1840.0
15.61	6800	133.8	1190.0	1860.0
15.66	6800	122.6	1190.0	1880.0
15.71	6800	115.8	1180.0	1910.0
15.76	6840	109.8	1180.0	1910.0
15.82	6880	103.0	1180.0	1900.0
15.87	6880	100.8	1180.0	1860.0
15.92	6920	97.0	780.0	1820.0
15.96	6880	72.2	690.0	1730.0
16.01	6840	52.6	560.0	1730.0
16.06	6880	38.3	290.0	1720.0